

BIAX 22/33



Biaxial mixer – Clean – Safe – Quick

- Mixing in closed containers: round/oval/square
- BIAXIAL high speed mixing process, short mixing times of less than 90 seconds even for heavy materials
- Maximum reliability due to sturdy design, 10,000 units already in service
- Attractive design in a stainless steel look
- Sliding door; space-saving and compatible with roller conveyors

Collomix[®]

- **Fully automatic process:
Clamp - Mix - Release**
- **Safety by clamping sensor**
- **Smooth operation using gentle
Biax technology**
- **Container table can be pulled out
full length**
- **User support using LCD display**
- **Easy to service thanks to easy
access and transport rollers**



BIAX 22 / 33



Technical Data

	BIAX 22	BIAX 33
Mixing capacity:	35 kg	35 kg
Container height:	60 - 350 mm	60 - 400 mm
Max. container diameter, bottom	365 mm	365 mm
Suitable for Oval Containers:	yes	yes
Lubrication:	Lubrication cartouche	Lubrication cartouche
Transport rollers:	yes	yes
Timer buttons:	Three programmable buttons	Three programmable buttons
Clamping pressure:	Programmable	Programmable
Programming Parameters:	with Machine keyboard	with Machine keyboard
Colour:	RAL 7016/Stainless steel	RAL 7016/Stainless steel
Motor power:	1,1 KW	1,1 KW
Power rate (standard):	230 V/50Hz	230 V/50Hz
(option):	115 V/60 Hz	115 V/60 Hz
Machine dimensions (w x d x h):	730 x 845 x 1060 mm	780 x 845 x 1100 mm
Machine weight:	200 kg	214 kg
Packaging dimensions:	1200 x 800 x 1235 mm	1200 x 800 x 1265 mm
Packaging weight:	227 kg	241 kg

Collomix®

04/07 Subject to technical change