

# MAKO 8

**The 8-page CTP for high quality imaging and press format flexibility at the lowest cost of operation**

Breaking the price barrier for 8-page CTP, the **MAKO 8** makes 8-page CTP affordable for all commercial printers. It covers all formats for 2, 4, 6 and 8-page signatures with resolutions from 1800 dpi to 3556 dpi, with the lowest operating cost in the industry. With a maximum format of 32.4" x 45.0" (824mm x 1143mm) and production speeds up to 15 Speedmaster 102 plates per hour, the MAKO 8 keeps multipress environments efficient through flexible, fast and trouble-free performance.

- The MAKO 8 employs an auto-pinch/auto-image feature for true hands-free operation after initial plate positioning.
- Supports press formats from 228mm x 252mm (8.9" x 9.9") to 824mm x 1143mm (32.4" x 45.0").

- Flexible – ECRM's patented press registration pin bars allow for both edge and notch registration, matching a wider range of press requirements.
- Open-ended software system accepts 1-bit TIFF files – choose the solutions you want. ECRM is here to help.
- No hidden extras – our online conveyor is standard on all MAKO CTP, allowing for a direct connection to the processor at no extra cost.
- Uses a straight-through plate path for easy operation and automated delivery to the processor.
- Bundled with CtServer Professional – ECRM's enhanced 1-bit TIFF server. Our open-ended software system accepts 1-bit TIFF files – choose the solutions you want. ECRM is here to help.
- Basic electricity requirements and quick installation – no dedicated power line needed. Lowest energy consumption in the industry – draws the same energy as a PC.
- Modular design keeps maintenance simple and costs low.
- Simple and intuitive operator interface makes training easy for everyone.



# Choose ECRM for your Violet CTP solutions

ECRM products offer the lowest total cost of ownership in the business and the highest quality performance in the industry. Our manufacturing facility is located in Tewksbury, Massachusetts, USA and is certified as being in conformity to ISO 9001:2000 standards. Our signature flexible design lets you decide what's best for your CTP system, workflow, plates and processors. We support you every step of the way and work with you to ensure complete system integrity.



## MAKO 8 CTP Specifications

<b>Plate Sizes</b>	Maximum: 824mm x 1143mm (32.4" x 45.0") Minimum: 228mm x 252mm (8.9" x 9.9")
<b>Plate Thickness</b>	0.14mm to 0.35mm (0.0055" to 0.014")
<b>Media Types</b>	Violet-sensitive photopolymer and silver halide metal plates. See media specifications for safe-light information.
<b>Recording Source</b>	Violet laser diode (405 nm), available for photopolymer or silver halide plates
<b>Resolutions</b>	Five resolutions from 1800 to 3556 dpi Resolutions include: 1800, 2400, 2540, 3048, and 3556dpi
<b>Maximum Line Screen</b>	Up to 200 lpi (78.7 lpcm). Media dependent
<b>Repeatability</b>	0.025mm (0.001") typical May vary according to media type and processing conditions
<b>Processing</b>	Online: The plate transport automatically moves the plate into the processor.
<b>Environmental</b>	Power: 100 - 240 Volts; 3 Amps; 250 watts maximum; 50/60Hz, single phase Heat Dissipation: 850 BTU/hour
<b>Operating Conditions</b>	62 - 86° F (17 - 30° C); relative humidity 45 - 65%, noncondensing. Relative humidity outside of this range may affect performance. Operating conditions outside plate media specifications may affect performance.
<b>Weight</b>	409 kg (900 lbs.)
<b>Footprint Dimensions</b>	Width: 106.7cm (42.0") Length: 244.8cm (96.4") Height: 189.2cm (74.5")

**ECRM**<sup>®</sup>  
imaging systems

### Headquarters:

554 Clark Road  
Tewksbury, MA 01876  
USA  
Tel: (+1) 978.851.0207  
Fax: (+1) 978.851.7016  
sales@ecrm.com  
[www.ecrm.com](http://www.ecrm.com)

### International Sales Offices:

3 Century Court, Tolpits Lane Watford, Hertfordshire WD18 9PU, UK Tel: (+44) 1923.218.255 Fax: (+44) 1923.218.256 sales_uk@ecrm.com	B2, 10/F, Block B, Kailey Industrial Centre, 12 Fung Yip Street, Chai Wan, Hong Kong Tel: (+852) 2564-8989 Fax: (+852) 2564-8821 sales_hk@ecrm.com sales_asia@ecrm.com
--	---

All ECRM products carry the CE mark. All products are CSA & CSA/NRTL Certified. Class 1 Laser Products ECRM's Tewksbury facility is ISO 9001:2000 certified.

All trademarks are the property of their respective owners and their use in this documentation is acknowledged and recognized. The information provided in this document is subject to change without notice.